

CHAIN



SPINNING CHAIN

BHDE regular link spinning chain is made from a special analysis alloy steel. A special controlled heat treating process gives the chain surface an abrasive resistant hardness.

Extra short links assure greater pipe contact and greater gripping power.

The BHDE spinning chain is proof-tested. The working load limits are as follows:

1/4"3500 pounds
5/16"4500 pounds
3/8"7100 pounds

CATHEAD CHAIN

BHDE cathead chain is produced from the same alloy steel as the BHDE spinning chain.

CONNECTING LINK



SPINNING CHAIN

SIZE	LENGTH FT.	WEIGHT LBS.	PART NO.
1/4"	14	11	K140140
1/4"	16	12	K140160
1/4"	18	14	K140180
1/4"	20	16	K140200
1/4"	22	18	K140220
1/4"	25	19	K140250
5/16"	16	15	K516160
5/16"	18	17	K516180
5/16"	20	19	K516200
5/16"	25	24	K516240

CAT HEAD CHAIN

SIZE	LENGTH FT.	WEIGHT LBS.	PART NO.
5/16"	24	23	K516024
5/16"	30	29	K516030
5/16"	33	32	K516033
3/8"	30	42	K380030
3/8"	33	46	K380033
3/8"	35	49	K380035
3/8"	40	56	K380040

Link Only528011
Nylon Tail5726-5427
Brass Link5427

All sizes of chain available in bulk shipments at special length prices in minimum quantities of 1000' in 1/4 and 5/16, 500' in 3/8.



A DIVISION OF BOB HERBERT & ASSOCIATES, INC.
www.bhde.com