

# SLEEVE COUPLINGS

## STANDARD SLEEVE COUPLINGS

Sleeve-type couplings provide a quick, flexible joint for plain-end pipe. A resilient gasket, made from oil and gas resistant Buna N, compresses around the pipe ends as bolts are tightened, resulting in a leak-proof, self-aligning seal. Styles 380 (short) and 400 (long) sleeve couplings consist of sleeve, gaskets, end caps, bolts, and nuts. All metal parts are painted for improved resistance to atmospheric corrosion.

SLEEVE COUPLINGS			
PART NO.	DESCR.	STYLE	WT.
DS2X5	2" x 5"	38	9
DS3X5	3" x 5"	38	12
DS4X5	4" x 5"	38	14
DS5X5	5" x 5"	38	21
DS6X5	6" x 5"	38	23
DS6X7	6" x 7"	38	27
DS8X7	8" x 7"	38	32
DS10X7	10" x 7"	38	38
DS12X7	12" x 7"	38	47
DS2x12	2" x 12"	40	13
DS3X12	3" x 12"	40	18
DS4X12	4" x 12"	40	20
DS6X12	6" x 12"	40	34
DS6X16	6" x 16"	40	41
DS8X12	8" x 12"	40	37
DS8X16	8" x 16"	40	53
DS10X16	10" x 16"	40	62
DS10X24	10" x 24"	40	85
DS12X16	12" x 16"	40	71
DS12X24	12" x 24"	40	95
DSG2	2"	-	0.25
DSG3	3"	-	0.3
DSG4	4"	-	0.5
DSG5	5"	-	0.6
DSG6	6"	-	0.6
DSG8	8"	-	0.7
DSG10	10"	-	0.8
DSG12	12"	-	1.0
DSB58X11	5/8" x 11"	-	1.2
DSB58X19	5/8" x 19"	-	1.8

**DS** = Steel Sleeve Coupling with Buna Gasket

**DSG** = Buna Gasket

**DSB** = Bolt with Nut



### Sleeve Coupling Specifications

Tube: Hot Roll 1010 Electric Weld  
 Fiberglass Epoxy Resin  
 High Density Polyethylene Pipe

Bolts/Washers/Nuts: Carbon Steel Zinc Plated

End Caps: HRP Steel B65

Gaskets: Buna-N, Maximum temperature is 200°F

### Also Available

- Scotchkote Sleeve Couplings
- Fiberglass Sleeve Couplings



A DIVISION OF BOB HERBERT & ASSOCIATES, INC.  
 www.bhde.com